


# Standard Resistors



Eventually all resistance thermometry refers back to one or more fixed resistors. These are a key element in any laboratory which measures temperature. The resistors need to be very stable with time, temperature and transportation, and they need to have negligible inductance and capacitance.

They also need to have a long and successful history of use.

Wilkins and Swan at our National Physical Laboratory (N.P.L.) developed a resistor design flexible enough to allow windings with various resistance values to be made available and stable enough to be accepted world-wide as resistance standards. Particularly important is that the AC/DC characteristics are the same up to about 1000 Hz.

This design has been licensed to H. Tinsley & Co. who have been producing (and have made further improvements to) this product since 1970.

Isotech are pleased to be able to offer this design of resistor made for us by Tinsley with 1 of 2 calibration possibilities:

UKAS with an uncertainty of  $\pm 0.3$ ppm. Refer to Databook 5 for details.

NPL with an uncertainty of  $\pm 0.1$  ppm (dependant on Ohmic value).

See page 41 for a suitable enclosure for your resistors.

TYPE S.R.A. Values	1, 10, 25 and 100 ohms
TYPE S.R.B. Values	1000, 10,000 ohms
Calibrated accuracy	0.3ppm (see UKAS schedule, Databook 5)
Accuracy of adjustment	$\pm 20$ ppm
Stability	2ppm/year (0.5ppm/year to special order)
Temperature coefficient of resistance	2ppm/ $^{\circ}$ C 0.5ppm to special order
Recommended dissipation	10 milliwatts
Maximum dissipation	1 watt
Approximate load coefficient	6ppm/watt
A.C./D.C. transfer error at 1kHz	1ppm for values 10 $\Omega$ , 25 $\Omega$ , 100 $\Omega$ , 1k $\Omega$ 5ppm for 1 $\Omega$ and 10k $\Omega$

## Construction

Element	Strain free, immersed in dry oil (No. 4 Kerosene)
Top panel	Bakelite with PTFE inserts and engraved lettering
Terminal - Current	0BA copper
Terminal - Potential	4BA copper
Earth	6BA brass
Dimensions	Container 114 x 76mm diameter Overall 140 x 83mm diameter
Weight	680 grammes

## How to order

Standard Resistor S.R.

Please specify type, resistance value and calibration option

